



Technical Data Sheet:

#PG-062

6.0mil Perforated Window Calendered Vinyl (60/40) with Removable Adhesive (White Print Face w/ Black Back)



PG-062 is a 6.0 mil perforated high performance vinyl film with a white print side and a black see through side coated with a clear low tack repositionable removable solvent acrylic pressure sensitive adhesive designed for exterior/outside mounted one way view-through window graphics. PG-062 can be used in solvent, eco-solvent, latex, UV-curable, screen, and offset UV-curable wide format digital printing. The dual layflat liner construction, perforated/solid liner, offers good dimensional stability in a variety of ambient conditions. The adhesive is designed to cleanly remove from glass with little to no adhesive residue. The most common application is temporary or medium term storefront retail/POP displays/advertisements. If you intend to use this window perf on vehicle windows, make sure to comply with local regulations regarding minimum light transmission. If you choose to laminate this product, an optically clear laminate such as our PG-424 is recommended.

Product Number	#062
Film	
Film Type	White/Black Perforated Vinyl
Finish	Matte
Hole Pattern	60/40
Film Thickness (mils)	6.0
Film Weight (gsm)	120
Adhesive	
Adhesive Type	Solvent Acrylic
Adhesive Thickness (mils)	1.0
Adhesive Color	Clear
Liner	
Liner Weight (#)	104
Liner Type	Dual Layer (Perforated/Solid) White 2-Sided PE-Coated Kraft
Liner Thickness (mils)	9.2

Environment	
Application Temperature	≥ 40°F
Service Temperature	0°F to 150°F
Outdoor Durability	2 years
Removability	1 year

*Note: In the following chart, checkmarks indicate compatibility, while cross marks indicate incompatibility.

Applications	Product Compatibility
✓ POP/Retail	✗ Wet Apply
✗ Wall	✓ Dry Apply
✗ Wrap	✗ Laminating
✓ Window	✗ Mounting
✗ Floor	✓ Die Cuttable
✓ General Signage	✗ Hot Stamp
✓ Indoor	✗ Thermal Dye
✓ Outdoor	✗ Flatbed Cuttable
	✗ OEM Painted Metal
	✗ Painted Aluminum
	✗ Stainless Steel
	✓ Acrylic
	✓ Glass