



Technical Data Sheet:

#PG-072

6.0mil Perforated Window Calendered Vinyl (70/30) with Removable Adhesive (White Print Face w/ Black Back)



PG-072 is a 6.0 mil perforated high performance vinyl film with a white print side and a black see through side coated with a clear low tack repositionable removable solvent acrylic pressure sensitive adhesive designed for exterior/outside mounted one way view-through window graphics. PG-072 can be used in solvent, eco-solvent, latex, UV-curable, screen, and offset UV-curable wide format digital printing. The dual layflat liner construction, perforated/solid liner, offers good dimensional stability in a variety of ambient conditions. The adhesive is designed to cleanly remove from glass with little to no adhesive residue. Some common applications include: temporary and medium-term POP storefront applications and advertisements. This vinyl film is not recommended for vehicle windows as this perforated window film does not meet the typical minimum light transmission regulations. In order to comply with light transmission regulations, we recommend our PG-323. If you intend to use a laminate for this product, it is recommended that you use an optically clear laminate such as our PG-424.

Product Number	#072
Film	
Film Type	White/Black Perforated Vinyl
Finish	Matte
Film Thickness (mils)	6.0
Film Weight (gsm)	135
Adhesive	
Adhesive Type	Solvent Acrylic
Adhesive Thickness (mils)	1.0
Adhesive Color	Clear
Liner	
Liner Weight (#)	106
Liner Type	Dual Layer (Perforated/Solid) White 2-Sided PE-Coated Kraft
Liner Thickness (mils)	9.2

Environment	
Application Temperature	≥ 40°F
Service Temperature	0°F to 150°F
Outdoor Durability	Up to 2 years
Removability	Up to 1 year clean removability (note that while removal difficulty increases with time after the 1 year date, this product is always removable). If removing this product after 1 year, use standard industrial grade adhesive removing chemicals.

*Note: In the following chart, checkmarks indicate compatibility, while cross marks indicate incompatibility.

Applications	Product Compatibility
✓ POP/Retail	✗ Wet Apply
✗ Wall	✓ Dry Apply
✗ Wrap	✗ Laminating
✓ Window	✗ Mounting
✗ Floor	✓ Die Cuttable
✓ General Signage	✗ Hot Stamp
✗ Vehicle	✗ Thermal Dye
✓ Outdoor	✓ Flatbed Cuttable
✓ Indoor	✗ OEM Painted Metal
	✗ Painted Aluminum
	✗ Stainless Steel
	✓ Acrylic
	✓ Glass