



Technical Data Sheet:

#PG-122

6.0mil Gloss White Semi-Rigid
Calendered Vinyl With Removable
Adhesive



PG-122 is a 6.0 mil gloss white semi-rigid vinyl with a low-tack removable acrylic pressure sensitive adhesive on a 90# liner. This product can be used in solvent, eco-solvent, latex, UV-curable, screen, and offset UV-curable printing. Semi-Rigid films are easy to handle due to their rigidity and thus can be applied quickly. Some common applications include: temporary interior or exterior signage, decals, nameplates, die-cut letters, temporary storefront applications requiring bond to windows, and point-of-purchase displays. Note that this vinyl film will always be removable, but after the 1 year clean removal timeline, you will likely have some percentage of adhesive transfer leftover.

Product Number	#122
Film	
Film Type	White Intermediate Vinyl
Finish	Gloss
Film Thickness (mils)	6.0
Film Weight (gsm)	200
Gloss (60°)	≥ 70
Opacity (%)	98
Adhesive	
Adhesive Type	Emulsion Acrylic
Adhesive Thickness (mils)	1.0
Adhesive Color	Clear
Liner	
Liner Weight (#)	90
Liner Type	White 2-Sided PE-Coated Kraft
Liner Thickness (mils)	6.7

Environment	
Application Temperature	≥ 40°F
Service Temperature	-40°F to 180°F
Outdoor Durability	Up to 3 years
Removability	Up to 1 year clean removability (some adhesive buildup will likely remain if removed after 1 year)

*Note: In the following chart, checkmarks indicate compatibility, while cross marks indicate incompatibility.

Applications	Product Compatibility
✓ POP/Retail	✗ Wet Apply
✗ Wall	✓ Dry Apply
✗ Wrap	✗ Laminating
✓ Window	✗ Mounting
✗ Floor	✓ Die Cuttable
✓ General Signage	✗ Hot Stamp
✗ Fleet	✗ Thermal Dye
✓ Outdoor	✓ Flatbed Cuttable
✓ Indoor	✓ OEM Painted Metal
	✓ Painted Aluminum
	✓ Stainless Steel
	✗ Low-energy Surfaces
	✓ Glass