



Technical Data Sheet:

#PG-303

3.4mil Matte White Calendered Vinyl with Low-Tack Removable Adhesive



PG-303 is a 3.4 mil polymeric matte white calendered vinyl coated with a clear low-tack removable acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This vinyl is designed to accept a variety of solvent-based, eco-solvent, latex and UV curable inks common to wide format digital printing systems. PG-303 is a removable vinyl designed for interior or exterior signage, decals, nameplates, and point-of-purchase displays. The 90# liner offers excellent product layflat in a variety of ambient conditions along with ease of application of large format graphics. Some applications for this product include: temporary interior or exterior signage, decals, nameplates, point-of-purchase displays and general signage. Not designed for coated/sealed/treated stainless steel, brass or bronze surfaces found on elevator doors.

Product Number	#303
Film	
Film Type	White Polymeric Vinyl
Finish	Matte
Film Thickness (mils)	3.4
Film Weight (gsm)	120
Gloss (60°)	≤ 20
Opacity (%)	93
Adhesive	
Adhesive Type	Emulsion Acrylic
Adhesive Thickness (mils)	1.0
Adhesive Color	Clear
Liner	
Liner Weight (#)	90
Liner Type	White 2-Sided PE-Coated Kraft
Liner Thickness (mils)	6.7

Environment	
Application Temperature	≥ 40°F
Service Temperature	-40°F to 180°F
Outdoor Durability	5 years
Removability	1 year

*Note: In the following chart, checkmarks indicate compatibility, while cross marks indicate incompatibility.

Applications	Product Compatibility
✓ POP/Retail	✗ Wet Apply
✗ Wall	✓ Dry Apply
✗ Wrap	✗ Laminating
✓ Window	✗ Mounting
✗ Floor	✓ Die Cuttable
✓ General Signage	✗ Hot Stamp
✓ Outdoor & Indoor	✗ Thermal Dye
✓	
✗ Fleet	✓ Flatbed Cuttable
✗ Translucent	✗ OEM Painted Metal
	✗ Painted Aluminum
	✗ Stainless Steel
	✓ Glass
	✓ Acrylic
	✗ Polyester
	✗ Low-energy Surfaces