



# Technical Data Sheet:

## #PG-802

### 7.0mil Gloss White Static Cling Soft Calendered Vinyl



PG-802 is a 7.0 mil premium white static cling flexible calendered vinyl film laminated to a 90# lay-flat liner. This product can be used in solvent, eco-solvent, latex, UV-curable, and screen printing. Offset printing is not recommended for PG-802. This static cling vinyl film may be used for temporary applications to exterior glass for up to 3 months. Temperature, wind and rain may also limit the bond of static cling vinyl to exterior windows. Some common applications include: window decals, temporary product markings, POP displays, and protective masking.

Product Number	#802
<b>Film</b>	
Film Type	White Static Cling (Monomeric) Vinyl
Finish	Gloss
Film Thickness (mils)	7.0
Film Weight (gsm)	220
Gloss (60°)	≥ 90
Opacity (%)	95
<b>Liner</b>	
Liner Weight (#)	90
Liner Type	White 2-Sided PE-Coated Kraft
Liner Thickness (mils)	6.7
<b>Environment</b>	
Application Temperature	≥ 40F
Service Temperature	-40F to 180F
Outdoor Durability	Up to 3 months
Removability	Up to 3 months

\*Note: In the following chart, checkmarks indicate compatibility, while cross marks indicate incompatibility.

Applications	Product Compatibility
✓ POP/Retail	✓ Wet Apply
✗ Wall	✓ Dry Apply
✗ Wrap	✗ Laminating
✓ Window	✗ Mounting
✗ Floor	✓ Die Cuttable
✓ General Signage	✗ Hot Stamp
✗ Fleet	✗ Thermal Dye
✓ Outdoor (Short Term)	✓ Flatbed Cuttable
✓ Indoor	✓ OEM Painted Metal
	✓ Acrylic
	✓ Glass
	✗ Polyester