



Technical Data Sheet:

#PG-611

1.0mil Clear Polyester Double-Sided Mounting Film with Perm/Air-Egress Removable Adhesive (Dual-Liner)



PG-611 is a double-coated pressure sensitive 1.0 mil clear polyester film with a high-tack permanent adhesive on one side and a high-tack removable adhesive on the other side. PG-611 has a 4.5 mil clear air egress PET liner printed with "Remove to Expose Adhesive" on the removable adhesive side. This air-egress liner assures smooth bubble free application (Note: air-egress adhesives are **dry apply only**). The clear liner allows the graphics to be viewed after lamination with PG-611. This product is designed for laminating thin flexible plastic films and papers commonly found in graphics for temporary application to glass. The high-tack permanent adhesive is protected by a 1.5 mil clear polyester liner. This clear mounting film can be laminated by the cold laminating process without the addition of heat. Please note that PG-611 is intended for application to glass, but may be used on other substrates; test for your specific uses. PG-611 can be used with graphic film and paper laminations and is not a structural mounting tape. PG-611 is designed to produce two sided decals using digital prints, screen printed and other printed images for application to glass. These decals are cleanly removable. In all cases the substrates must be clean and free of dust, dirt and oil. This mounting film is not recommended for tinted or laminated windows.

Product Number	#611
Film	
Film Type	Clear Polyester
Film Thickness (mils)	1.0
Film Weight (gsm)	32
Adhesive	
Adhesive Type	Solvent Acrylic (Remov. Side) / Emulsion Acrylic (Perm. Side)
Adhesive Thickness (mils)	Remov. Side: 0.7 Perm Side: 0.9
Adhesive Color	Clear
Liner	
Liner Type	Clear Printed Polyester/Air-egress (Remov. Side) / Clear Polyester (Perm. Side)
Liner Thickness (mils)	Remov. Side: 4.5 Perm Side: 1.5

Environment	
Application Temperature	≥ 40°F
Service Temperature	-40°F to 180°F
Outdoor Durability	1 year
Removability	6 months

*Note: In the following chart, checkmarks indicate compatibility, while cross marks indicate incompatibility.

Applications	Product Compatibility
✓ POP/Retail	✗ Wet Apply
✗ Wall	✓ Dry Apply (Air-egress side)
✗ Wrap	✗ Laminating
✓ Window	✓ Mounting
✗ Floor	✗ Die Cuttable
✓ General Signage	✗ Hot Stamp
✓ Outdoor (Short Term)	✗ Thermal Dye
✗ Translucent	✗ Flatbed Cuttable
	✗ OEM Painted Metal
	✗ PVC
	✓ Acrylic
	✗ Polyester
	✓ Glass