



Technical Data Sheet:

#PG-902

3.5mil Matte White Calendered Vinyl with High-Tack Opaque Removable Adhesive



PG-902 is a 3.5 mil matte white polymeric flexible opaque vinyl film coated with a removable acrylic pressure-sensitive adhesive on a 90# layflat liner. This product can be used in solvent, eco-solvent, latex, UV-curable, screen, offset UV-curable printing, and offset conventional printing. PG-902 is designed for temporary applications including product markings, point of purchase decals, transportation advertising systems, and tri-vision indoor/outdoor billboard displays. PG-902 will conform to simple curves and has excellent hiding characteristics for multi-layered graphics. The adhesive formulation allows for installation on glass and OEM painted metal with a surface temperature of 20°F. This vinyl film is commonly used for transit-related applications including king/queen/tail bus advertisements, opaque removable graphics, and layered poster graphics.

Product Number	#902
Film	
Film Type	White Polymeric Vinyl
Finish	Matte
Film Thickness (mils)	3.5
Film Weight (gsm)	130
Gloss (60°)	≤ 20
Opacity (%)	99
Adhesive	
Adhesive Type	Emulsion
Adhesive Thickness (mils)	1.0
Adhesive Color	Clear
Liner	
Liner Weight (#)	90
Liner Type	White 2-Sided PE Coated Kraft
Liner Thickness (mils)	6.7

Environment	
Application Temperature	≥ 20°F
Service Temperature	-40°F to 180°F
Outdoor Durability	Up to 5 years

*Note: In the following chart, checkmarks indicate compatibility, while cross marks indicate incompatibility.

Applications	Product Compatibility
✓ POP/Retail	✗ Wet Apply
✓ Wall	✓ Dry Apply
✓ Wrap (Simple Curves)	✗ Laminating
✗ Wrap (Complex Curves)	✗ Mounting
✓ Window	✓ Die Cuttable
✗ Floor	✗ Hot Stamp
✓ General Signage	✗ Thermal Dye
✓ Transit	✓ Flatbed Cuttable
✓ Outdoor (Long Term)	✓ OEM Painted Metal
✗ Translucent	✓ Painted Aluminum
	✓ Stainless Steel
	✓ Fiberglass