



Technical Data Sheet:

#PG-923

9.0mil Wall Film Matte White
Polyester Fabric with Removable
Repositionable Adhesive



PG-923 is a 9.0 mil wall film composed of a matte white polyester fabric with clear removable repositionable acrylic adhesive. PG-923 has the benefits of being easy to put up and easy to take down, can be applied without bunching or bubbling in one easy step (and will not stretch out), is scratch resistant, extremely durable, water resistant, ultra strong, and can be used on smooth walls. This product can be used in aqueous (pigment and dye), latex, and UV-curable wide format digital printing. Common applications for PG-923 include: interior walls, contour cut characters, short term indoor floor graphics, and POP/retail signage.

| Product Number | #923 |
|------------------------|----------------------------|
| Film | |
| Film Type | White Polyester |
| Finish | Matte |
| Film Thickness (mils) | 9.0 |
| Film Weight (gsm) | 226 |
| Gloss (60°) | 3 |
| Opacity (%) | 95 |
| Brightness | 96 (ISO Blue Whiteness) |
| Whiteness | 110 (CIE Ganz) |
| Adhesive | |
| Adhesive Type | Removable Acrylic Adhesive |
| Adhesive Color | Clear |
| Liner | |
| Liner Weight (#) | 108 |
| Liner Type | PE Coated on Both Sides |
| Liner Thickness (mils) | 5.0 |

| | |
|---------------------|---|
| Environment | |
| Outdoor Durability | Up to 6 months |
| Removability | Removable up to anywhere between 6 months - 1 year (the longer you go, the more permanent the product becomes, and the more difficult to remove). |
| Applications | |
| ✓ POP/Retail | ✓ Smooth Interior Walls |
| ✓ Outdoor & Indoor | ✓ Short Term Indoor Floor Graphics |